

AMP-5000X HIGH POWER AMPLIFIER FOR 2.4 GHz

This amplifier will give full 5 W RF power output at 12V! Amplifier AMP-5000X needs power supply is 12-16 V/ 1.6 A battery or DC power. It comes with a 1-year warranty. The output / input connectors are an SMA type. Power input 800 mW / 5 W. Maximum power input 1200 mW! Please use REGULATED POWER SUPPLY ONLY OR BATTERIES 12 V.

FEATURES:

- ◆ SIZE: 4.7" x 2.6" x 1.6"
- ♦ BATTERY POWERED 9 V 12 V
- ♦ CURRENT CONSUMPTION 1600mA/12V
- ♦ 5 W RF POWER TESTED!
- ♦ HIGH STABILITY
- ◆ TEMPERATURE RANGE -40+70*C
- ♦ REVERSE POLARITY PROTECTED
- ♦ 1 Y WARRANTY



NOTE: DO NOT CONNECT POWER IF ANTENNA (LOAD) IS NOT CONNECTED!

TEST RESULTS:

- ♦ FREQUENCY: 2350 MHz
- ♦ OUTPUT RF POWER 5.2 W
- ♦ INPUT POWER 800 mW
- ♦ HARMONIC SUPPRESSION TYP 30dBc
- ♦ OPERATING VOLTAGE 12-16 V DC
- ♦ MAX. CURRENT CONS. 1.6 A

Copyright © 2001-2014 RF-LINKS